

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

ABSTRACT

AN OPTICAL WAVEGUIDE STRUCTURE

5 An optical waveguide structure according to the invention comprises a core layer having a first refractive index n_{core} , an array of sub-regions within the core having a second refractive index n_{rods} , the array of sub-regions giving rise to a photonic band structure within the core layer, and a cladding layer adjacent to the core layer having a refractive index n_{cladding} , wherein:

10 $n_{\text{core}} > n_{\text{rods}} \geq n_{\text{cladding}}$ and $n_{\text{core}} - n_{\text{rods}} > 0.1$.

The structure of the present invention is less lossy than prior waveguide structures having photonic bandstructure regions. The out of plane divergence of light in the sub-regions is reduced as compared with air holes which are typically used in photonic crystal structures. As a result more light is coupled back into the core at the sub-region/core interface. Coupling of light into the buffer layer is also reduced. Furthermore, there are added advantages over the prior art associated with the fabrication of these structures.

(Figure 2)